



BODY 120 SILICONE

Technical Data Sheet No 705

General Technical Description

Superb adhesion ability, permanent elasticity

Long life resistance especially to peculiar weather conditions

Easily applicable

Surface

This is an acetate system, used for bonding, filling and sealing of joints over beton, metal sheets, ceramics, wood, glass and plastics. It has superb adhesion ability, gives permanent elasticity and a long life resistance especially to peculiar weather conditions. It can be easily applied with the cartridge, over dry surfaces which have been cleaned from oils and dust previously.

Pretreatment / Cleaning of substrate



Clean substrate using a soft cloth and BODY 770 ANTISIL NORMAL/BODY 771 ANTISIL FAST.

Make sure the surface is first wiped then air dried.



Make sure you always use appropriate face protection and good ventilation

Product Application:

»» Applied over dry surfaces which have been cleaned from oils and dust previously. Easily applicable. Suitable for bonding, filling and sealing of joints over beton, metal sheets, ceramics, wood, glass and plastics.



Always close tin after use



Protect from humidity



Apply using the cartridge



Always wear protective equipment



Drying time
17h /23°C (73°F)



Follow the application instructions mentioned in this TDS

Flash Point:
70°C/ 158°F

Specific Gravity:
0.98 g/cm³

Solid Content (No thinner):
83% Weight

VOC (2004/42/EC)
This product is a special refinish product based on its ingredients and its properties. The maximum VOC content in this category is 840 g/L. The VOC content in the ready for use form of this product is 150 g/L.
2004/42/IIIB(e)(840)150

Theoretical Coverage:
-

Cleaning of equipment:
Clean after final use with Body 740 ACRYL NORMAL

Remarks:

- Allow for additional time for combi spray booths to reach the desired temperature
- Best results when used with HB BODY PRODUCTS
- It can be used by countries that do not adopt the VOC legislation as well.

Storage shelf life:

- Store in a cool place +5°C - +25°C (+41°F - +77°F) and use within 12 months for best results. Guaranteed shelf life of 24 months in unused original containers

For professional use only. The information displayed on this sheet has been carefully selected through a series of laboratory investigations. It is based on our best knowledge at the time of issue. The data is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check for newer updates or further information if needed for his intended purpose. The intellectual property of this product, trademarks and copyrights is protected. All rights reserved. The relevant Material Safety Data Sheet and warnings displayed on the label must be read carefully. We may modify and / or discontinue operation of all or portions of this information at any time in our sole discretion, without any notice and assume no responsibility to update the information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

Issue 2 / 2017, December 2017